

Connector assembly N - Cable Socket

AIRCOM PLUS[®]

1.



Cut the cable end perpendicularly

2.



Slip the nut, the pressure ring and the rubber gasket over the cable end.

Hint: With a small amount of vaseline the rubber gasket will slide more easily.

3.



Remove 6 mm of the PVC sheath from the end of the cable with a knife.

4.



Bend copper braid at 90 degrees to cable body. Push in contact ferrule between copper foil and braid until stop. Trim braid even to rim of ferrule. Slide rubber gasket down to the contact ferrule.

5.



Remove foil and dielectric with a knife.

6.



Slide center pin (Pin 1, 2,8mm Ø) on center conductor and solder carefully. Then attach teflon isolator.

Hint: Pin 2 (3,0 mm Ø) is meant for ECOFLEX 10.

7.



Slide the prepared cable end into the connector housing until stop. Tighten smoothly with two wrenches 17 mm and 18 mm so that there is still a small gap visible between the nut and the connector housing.



NETHERLANDS

Roermond | www.classicinternational.nl

Tel. +31 (0)475-327390

GERMANY

Mönchengladbach | www.classicinternational.de

Tel. +49 (0)2166-33061

Connector assembly N-Plug

AIRCOM PLUS[®]

1.



Cut the cable end perpendicularly

2.



Slip the nut, the pressure ring and the rubber gasket over the cable end.

Hint: With a small amount of vaseline the rubber gasket will slide more easily.

3.



Remove 6 mm of the PVC sheath from the end of the cable with a knife.

4.



Bend copper braid at 90 degrees to cable body. Push in contact ferrule between copper foil and braid until stop. Trim braid even to rim of ferrule. Slide rubber gasket down to the contact ferrule.

5.



Remove foil and dielectric with a knife.

6.



Slide center pin (Pin 1, 2,8mm Ø) on center conductor and solder carefully. Then attach teflon isolator.

Hint: Pin 2 (3,0 mm Ø) is meant for ECOFLEX 10

7.



Slide the prepared cable end into the connector housing until stop. Tighten smoothly with two wrenches 17 mm and 18 mm so that there is still a small gap visible between the nut and the connector housing.



NETHERLANDS

Roermond | www.classicinternational.nl

Tel. +31 (0)475-327390

GERMANY

Mönchengladbach | www.classicinternational.de

Tel. +49 (0)2166-33061